

DRIVEN BY AIR.



# SuperFlex Hose Assemblies

Introducing the new super flexible hose assembly from PCL.



PCL's new 9.5mm (3/8") SuperFlex hose assemblies are extremely flexible, durable and protected against wearing.

## Key Features & Benefits

- Extremely flexible with good anti-kink characteristics - Minimum air flow loss
- Soft touch for excellent handling - Increased comfort for the user
- Durable with excellent ageing and ultra-violet resistance - Increased service life
- Highly resistant to a wide range of acids and alkalis - A wide range of applications
- 3:1 safety factor @ -15°C + 60°C


## Approvals

Complies to: RoHS 3

## Specification

Service temperature: -15°C to + 60°C

Hose Inside Diameter: 9.5 mm



[www.pclairtechnology.com](http://www.pclairtechnology.com)

A HORNGROUP BRAND

**Superflex Hose with Standard Adaptor & Vertex Coupling**

Part Number	Hose Length	Hose I.D.
HA2133SF	5 m	9.5 mm
HA2134SF	10 m	9.5 mm
HA2139SF	15 m	9.5 mm
HA2129SF	20 m	9.5 mm



**Superflex Hose with XF Adaptor & XF Coupling**

Part Number	Hose Length	Hose I.D.
HA2140SF	5 m	9.5 mm
HA2141SF	10 m	9.5 mm
HA2142SF	15 m	9.5 mm
HA2143SF	20 m	9.5 mm



**Superflex Hose**

Part Number	Hose Length	Hose I.D.
HS25B01SF	5 m	9.5 mm
HS25C01SF	10 m	9.5 mm
HC25D01SF	15 m	9.5 mm
HC25E01SF	20 m	9.5 mm
HC25X01SF	100 m	9.5 mm



**Superflex Hose with Swivel end fittings**

Part Number	Hose Length	Hose I.D.
HA2043SF	5 m	9.5 mm
HA2044SF	10 m	9.5 mm
HA2045SF	15 m	9.5 mm
HA2046SF	20 m	9.5 mm



PCL is the world leader in the design and manufacture of tyre inflation and compressed air products.